



PRODUCT TECHNICAL DATA SHEET

SP289 BLACK LABEL SERIES L³ Moly PTFE Lubricant Protectant

DESCRIPTION: This lubricant is formulated with PTFE and fortified with Moly to provide long lasting lubrication and protection from friction, wear and corrosion. The light viscosity of this product allows for deep penetration into hard to reach moving parts. Safe for use on most surfaces.

- USES:**
- Penetrates and protects metal against rust and corrosion
 - Ideal for extreme conditions

SPECS:	Can Size: 20 Oz.
	Net Weight: 15 Oz.
	Shipping Weight: 18 lbs.
	Packaged: 12 cans per case
	UPC Number: 0 41911 00289 9

PHYSICAL CHARACTERISTICS:	Color: Gray, black
	Fragrance: Characteristic
	Shelf Life: 1 Year +

REGULATORY:	Ozone Depleting Compounds: None
	Recyclable Packaging: Yes
	VOC Compliant CARB/OTC: Yes
	CPSC Flame Extension: Not required to be labeled as flammable per 16 CFR 1500.
	DOT Hazard Certification: ORM-D
	Shipping Name: Consumer Commodity
	24 HOUR MEDICAL EMERGENCY: 1-866-836-8855

- PRODUCT FEATURES:**
- Fast-acting
 - Heat stable to 500°F
 - Displaces moisture
 - Protects metal



Manufactured by:
SPRAYWAY, INC.
1005 Westgate Drive • Addison, IL 60101
800-332-9000 • Fax: 630-543-7797 • www.spraywayblack.com