



PRODUCT TECHNICAL DATA SHEET

SW077 All Purpose Dry Lubricant & Release Agent

DESCRIPTION: The dry lubricant & release agent stops sticking and retards corrosion. This silicone spray eliminates annoying squeaks in hinges, latches, springs, etc. It leaves no greasy or oily film and is not affected by water or oil. The heat stable formula will not freeze or melt.

USES: It protects battery terminals, tools, aluminum windows and doors. An excellent release agent for plastic injection and compression moldings. Use on any surface: metal - glass - rubber - plastic - painted surfaces - fabrics.

SPECS:	Can Size: 20 Oz.
	Net Weight: 12 Oz.
	Shipping Weight: 13 lbs.
	Packaged: 12 cans per case
	UPC Number: 0 41911 00077 2

PHYSICAL CHARACTERISTICS:	Color: Colorless
	Fragrance: Solvent
	Shelf Life: 1 Year +

REGULATORY:	Ozone Depleting Compounds: None
	Recyclable Packaging: Yes
	VOC Compliant CARB/OTC: Yes
	CPSC Flame Extension: Required to be labeled as extremely flammable per 16 CFR 1500.
	DOT Hazard Class: ORM-D
	Shipping Name: Consumer Commodity
	24 HOUR MEDICAL EMERGENCY: 1-866-836-8855

- PRODUCT FEATURES:**
- Fast drying
 - Leaves no greasy or oily film
 - Heat stable - will not freeze or melt
 - Use on any surface



Manufactured by:
SPRAYWAY, INC.
 1005 Westgate Drive • Addison, IL 60101
 800-332-9000 • Fax: 630-543-7797 • www.spraywayinc.com