



PRODUCT TECHNICAL DATA SHEET

SW735 Rubberized Undercoating Spray

DESCRIPTION: No. 735 Rubberized Undercoating Spray is an ideal protectant for coating fender replacements, new panels, section repairs and weld joints. Leaving a paintable surface, the spray prevents rust, deadens sound and seals out moisture quickly and easily. In addition, it resists salt corrosion.

USES: Other uses for the undercoating spray include: crack sealer for concrete and asphalt drive-ways; gutter and flashing sealer; roof patch; planters; post and wood preserver; tree wound dressing.

SPECS:	Can Size: 20 Oz.
	Net Weight: 16 Oz.
	Shipping Weight: 16 lbs.
	Packaged: 12 cans per case
	UPC Number: 0 41911 00735 1

PHYSICAL CHARACTERISTICS:	Color: Black liquid
	Fragrance: Petroleum odor
	Shelf Life: 1 Year +

REGULATORY:	Ozone Depleting Compounds: None
	Recyclable Packaging: Yes
	VOC Compliant CARB/OTC: Yes
	CPSC Flame Extension: Required to be labeled as extremely flammable per 16 CFR 1500.
	DOT Hazard Class: ORM-D
	Shipping Name: Consumer Commodity
	24 HOUR MEDICAL EMERGENCY: 1-866-836-8855

- PRODUCT FEATURES:**
- *Seals out moisture*
 - *Retards rust*
 - *Deadens sound*
 - *Paintable*



Manufactured by:
SPRAYWAY, INC.
 1005 Westgate Drive • Addison, IL 60101
 800-332-9000 • Fax: 630-543-7797 • www.spraywayinc.com