

315 METAL-FREE FLOOR FINISH

The Metal-Free Floor Finish is an environmentally preferred floor coating that can be used on most hard resilient floors as a sealer/finish. Its low odor qualities make it a preferable product for health care, hospitals, nursing homes and school facilities.

This finish dries to a smooth, hard and colorless coating in 30 minutes under normal conditions. This finish is versatile and can be maintained using traditional maintenance procedures including scrub/re-coat or high speed bur-nishing.

- Non-flammable
- Safe in septic systems
- Readily biodegradable
- Low aquatic toxicity
- No ozone depleting substances
- Phosphate free
- No harmful chemical runoff
- Low V.O.C. content
- Non toxic

APPEARANCE: Milky white
pH (as concentrate): typically 7.5 - 8.5
Specific Gravity: typically 1.00

DOES NOT CONTAIN:

- Abrasives • Caustic alkalis • Agressive biocides • Harmful chemicals • Chlorinated solvents



APPLICATION METHODS:

Thoroughly clean the floor prior to applying this products.

1. Strip floors using Sprayway No. 316 Floor Finish Remover to remove build ups of old finishes, sealers or waxes.
2. Thoroughly rinse with cold water and let floor dry.
3. Apply thin to medium even coats of No. 315 with an appropriate finish mop or applicator.
4. Allow each coat to dry before applying next coat. Drying time under normal conditions is 30 minutes.
5. Apply a maximum of 4 - 6 coats in a 24-hour period.

Coverage - 3000 sq. ft. per gallon.

See label for other directions for use.



This product has been formulated in a partnership with the Design for the Environment Program.



This product meets the Green Seal™ environmental standard for industrial and institutional cleaners based on its reduced human and environmental toxicity and reduced volatile organic compound content.



Certified Floor Care Products CCD-147